Patrol Manager kit



Kontrolne točke/Tagovi



Security Guard Management Software

Jednostavnost, Inteligencija, Vizualizacija





Svjetlosni signal + Vibracija

Signalizacija:

- očitanja
- slabe baterije
- pune baterije







Drive-Free Magnetski USB

IP67 metalno kućište presvučeno silikonom





IP67



Dhatter-resistant



Tehničke karakteristike:

Dimenzije	144mm × 47mm × 30mm težina 200g
Kapacitet memorije	16Mbit flash, 60,000 očitanja
Baterija	3.7V/880mAh punjiva litijska baterija
IP zaštita	IP67
Radna temperatura	-40°C~+85°C
RFID standard	RFID 125KHz domet očitanja 3cm - 5cm
Komunikacija	Pogo pin USB(Drive-Free),15000 upload zapisa/min
Vijek baterije	1. Očitanje 1 zapis/s, 40 sati korištenja. 2. Očitanje 500 zapisa/dan, 30 dana korištenj a.
Signalizacija	Vibracija s LED svjetlom u boji (Crveno/Zeleno/ Plavo)
ID kod taga	1. 8-bit heksadecimalni broj (4 bytes) u čitaču. 10- znamenkasti dekadski broj u software-u. 2. Moguće proširenje na 10-bit heksadecimalni broj (5 bytes).

